

NH-310H(Master) / NH-310S(Slave) Performance Table

NH-310H(Master) to NH-310S(Slave): (Packet Error Rate=0)

| Item | Attn (db) | Rate(Mbps) | Link Quality | Item | Attn (db) | Rate(Mbps) | Link Quality |
|------|-----------|------------|--------------|------|-----------|------------|--------------|
| 1 | 10 | 192 | Green | 34 | 43 | 192 | Green |
| 2 | 11 | 192 | Green | 35 | 44 | 192 | Green |
| 3 | 12 | 192 | Green | 36 | 45 | 192 | Green |
| 4 | 13 | 192 | Green | 37 | 46 | 192 | Green |
| 5 | 14 | 192 | Green | 38 | 47 | 192 | Green |
| 6 | 15 | 192 | Green | 39 | 48 | 192 | Green |
| 7 | 16 | 192 | Green | 40 | 49 | 192 | Green |
| 8 | 17 | 192 | Green | 41 | 50 | 192 | Green |
| 9 | 18 | 192 | Green | 42 | 51 | 192 | Green |
| 10 | 19 | 192 | Green | 43 | 52 | 192 | Green |
| 11 | 20 | 192 | Green | 44 | 53 | 160 | Green |
| 12 | 21 | 192 | Green | 45 | 54 | 160 | Green |
| 13 | 22 | 192 | Green | 46 | 55 | 160 | Green |
| 14 | 23 | 192 | Green | 47 | 56 | 160 | Green |
| 15 | 24 | 192 | Green | 48 | 57 | 160 | Green |
| 16 | 25 | 192 | Green | 49 | 58 | 128 | Green |
| 17 | 26 | 192 | Green | 50 | 59 | 128 | Green |
| 18 | 27 | 192 | Green | 51 | 60 | 128 | Green |
| 19 | 28 | 192 | Green | 52 | 61 | 64 | G Y |
| 20 | 29 | 192 | Green | 53 | 62 | 64 | G Y |
| 21 | 30 | 192 | Green | 54 | 63 | 64 | G Y |
| 22 | 31 | 192 | Green | 55 | 64 | 64 | G Y |
| 23 | 32 | 192 | Green | 56 | 65 | 64 | G Y |
| 24 | 33 | 192 | Green | 57 | 66 | 64 | G Y |
| 25 | 34 | 192 | Green | 58 | 67 | 64 | G Y |
| 26 | 35 | 192 | Green | 59 | 68 | 64 | G Y |
| 27 | 36 | 192 | Green | 60 | 69 | 64 | G Y |
| 28 | 37 | 192 | Green | 61 | 70 | 64 | G Y |
| 29 | 38 | 192 | Green | 62 | 71 | 64 | G Y |
| 30 | 39 | 192 | Green | 63 | 72 | 0 | Yellow |
| 31 | 40 | 192 | Green | 64 | 73 | 0 | Yellow |
| 32 | 41 | 192 | Green | 65 | 74 | 0 | Yellow |
| 33 | 42 | 192 | Green | 66 | 75 | 0 | Yellow |

NH-310S(Slave) to NH-310H (Master): (Packet Error Rate=0)

| Item | Attn (db) | Rate(Mbps) | Link Quality | Item | Attn (db) | Rate(Mbps) | Link Quality |
|------|-----------|------------|--------------|------|-----------|------------|--------------|
| 1 | 10 | 224 | Green | 34 | 43 | 224 | Green |
| 2 | 11 | 224 | Green | 35 | 44 | 224 | Green |
| 3 | 12 | 224 | Green | 36 | 45 | 224 | Green |
| 4 | 13 | 224 | Green | 37 | 46 | 192 | Green |
| 5 | 14 | 224 | Green | 38 | 47 | 192 | Green |
| 6 | 15 | 224 | Green | 39 | 48 | 192 | Green |
| 7 | 16 | 224 | Green | 40 | 49 | 192 | Green |
| 8 | 17 | 224 | Green | 41 | 50 | 192 | Green |
| 9 | 18 | 224 | Green | 42 | 51 | 192 | Green |
| 10 | 19 | 224 | Green | 43 | 52 | 160 | Green |
| 11 | 20 | 224 | Green | 44 | 53 | 160 | Green |
| 12 | 21 | 224 | Green | 45 | 54 | 160 | Green |
| 13 | 22 | 224 | Green | 46 | 55 | 160 | Green |
| 14 | 23 | 224 | Green | 47 | 56 | 160 | Green |
| 15 | 24 | 224 | Green | 48 | 57 | 128 | Green |
| 16 | 25 | 224 | Green | 49 | 58 | 128 | Green |
| 17 | 26 | 224 | Green | 50 | 59 | 128 | Green |
| 18 | 27 | 224 | Green | 51 | 60 | 64 | G Y |
| 19 | 28 | 224 | Green | 52 | 61 | 64 | G Y |
| 20 | 29 | 224 | Green | 53 | 62 | 64 | G Y |
| 21 | 30 | 224 | Green | 54 | 63 | 64 | G Y |
| 22 | 31 | 224 | Green | 55 | 64 | 64 | G Y |
| 23 | 32 | 224 | Green | 56 | 65 | 64 | G Y |
| 24 | 33 | 224 | Green | 57 | 66 | 64 | G Y |
| 25 | 34 | 224 | Green | 58 | 67 | 64 | G Y |
| 26 | 35 | 224 | Green | 59 | 68 | 64 | G Y |
| 27 | 36 | 224 | Green | 60 | 69 | 32 | Yellow |
| 28 | 37 | 224 | Green | 61 | 70 | 32 | Yellow |
| 29 | 38 | 224 | Green | 62 | 71 | 32 | Yellow |
| 30 | 39 | 224 | Green | 63 | 72 | 0 | Yellow |
| 31 | 40 | 224 | Green | 64 | 73 | 0 | Yellow |
| 32 | 41 | 224 | Green | 65 | 74 | 0 | Yellow |
| 33 | 42 | 224 | Green | 66 | 75 | 0 | Yellow |

Notes:

1. The performance data above is for reference only, the actual data rate of the EOC Master/Slave's will vary depending on the quality of the coaxial cable and environment factors.
2. We recommend using RG59 75 ohm coaxial cable and link established under -145dBm/Hz noise floor.