



NV-600A

Managed VDSL2 CPE Router

NV-600A is a managed VDSL2 CPE router equipped with four Gigabit LAN ports. It is compliant to ITU-T G.993.2 and G.993.5 standards and supports VDSL2 30a profile that features 100Mbps of symmetric data and it is perfectly suitable for triple-play applications. NV-600A is a cost effective solution that delivers high-speed Internet access to end-users over existing copper wire infrastructure and is designed to meet the ISPs requirements with future proof Vectoring and ADSL2+ compatibility to cover end users in different loop range areas.

Features

- Supports G.993.5 Vectoring and ADSL2+
- Interoperable with major VDSL2 chipsets
- Supports up to VDSL2 profile 30a
- Supports up to 100 Mbps symmetric
- Supports Dying Gasp
- Supports SNMP v1/ v2c /v3
- Supports 802.1q VLAN tagging
- Configuration backup and restoration
- Security protection with firewall
- Supports Router and Bridge mode
- Supports Dual Firmware Image Backup

Specifications

Physical Interface	IEEE 802.3 10Base-T, 802.3u 100Base-TX, and 802.3z 1000Base-TX 4x RJ-45 10/100/1000Mbps MTU: 1680 bytes (Jumbo frame) 1x RJ-11 for POTS/ISDN Reset Button (Factory Reset)
VDSL2 Interface	Complies with ITU-T G993.2, G993.5 Connector: RJ-11/Terminal block PTM/ATM Transmission On-board surge protection
Indicators	LAN: Act/Link, Power; VDSL2: Act/Link
QoS	8 queues MFC/DSCP 802.1p VLAN priority

Routing	IP Multicast, IGMP Proxy, Snooping Static Routing IPv4, IPv6 forwarding DHCP Server/Relay/Client IPv4/IPv6 DNS Proxy and Relay, NTP Client
Firewall	IPv6 Firewall Packet, URL filtering Parental Control, DMZ Host
Power	DC 12V
Dimensions	184 x 146 x 40 mm (7.2" x 5.74" x 1.57")
Temperature	0~50°C (Operating), -20~70°C (Storage)
Humidity	10 - 90% non-condensing
Certification	CE, FCC, RoHS Compliant

Application

Point to Point

